

Conformal Coated

Selection Guide



LNX-800AG-T-CC



LNX-C500-CC



LNX-800A-T-CC



LNP-1002G-SFP-T-CC



LMX-1204G-SFP-T-CC

Technical Information

Number of Ports	8	5	8	10	12
10/100Base-TX	-	5	8	-	-
10/100/1000Base-TX	8	-	-	8	8
100/1000Base-X SFP	-	-	-	2	4
IEEE 802.3at PoE (P.S.E.)	-	-	-	8	-
Jumbo Frame Support	✓	-	✓	✓	✓

Power Requirements

Redundant Power Inputs	12V-48VDC	12V-48VDC	12V-48VDC	45V-55VDC	12V-48VDC
Overload Current Protection	✓	✓	✓	✓	✓
Reverse Polarity Protection	✓	✓	✓	✓	✓

Mechanical Characteristics

Housing	Metal, IP30 protection	Metal, IP30 protection	Metal, IP30 protection	Metal, IP30 protection	Metal, IP30 protection
Dimensions (WxHxD mm)	30x140x95	26x95x75	30x140x95	46x142x99	54x142x99
Din-Rail & Panel Mounting	✓	✓	✓	✓	✓

Operating Temperature

Standard (-10 to 65°C)	✓	✓	✓	✓	✓
Extended (-40 to 75°C)	✓	✓	✓	✓	✓

Standards & Certifications

EN 61000-6-4 / EN 61000-6-2	✓	✓	✓	✓	✓
FCC Part 15B / CISPR 22	✓	✓	✓	✓	✓
Conformal Coated	✓	✓	✓	✓	✓

